





## Safety torch with intelligent energy management

Robust, reliable and ultralight. Certified ATEX ZONE 1/21 to be used in the most dangerous areas and confined spaces, the torch combines a photoluminescent bezel with a light sensor enabling the user to save battery and improve the torch burning time.

































ATEX: II 2G Ex ia op is IIC T4 Gb II 2D Ex ia op is IIIC T85 °C Db GAS ZONE 1 | 2 DUST ZONE 21 | 22

Ingress protection: IP67

Weight: Rechargeable model: 125 gr.

(battery included) Alkaline model: 145 gr. (AAA batteries included)

**Measures:** 150 x 38 x 44 mm.

Burning time: Rechargeable model 4 h Alkaline model up to 30 h

Torch body material: Thermoplastic resin with high resistance to the impacts, extreme temperatures and corrosive substances

Lighting source: 135 lumens

On/Off button: Made of soft touch material, it's placed on the side to guarantee easy finding and pushing with gloves

## 2 MODELS AVAILABLE

• IL-3



·LS



Rechargeable battery Lithium | Li-ion / 3,7 V (included)

**3 CHARGERS AVAILABLE** OF 1, 3 AND 5 POSITIONS (Only for IL-3R)









The Adalit IL-3R torch integrates an automatic power device that helps localizing it when charging

When a power failure to the charger occurs or the torch is taken from the charger, the torch switches on automatically remaining in this state up to 4 hours







www.adalit.com

